



PERMIT #: \_\_\_\_\_

ADDRESS: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

OWNER: \_\_\_\_\_

### **HURRICANE MITIGATION RETROFIT FORM**

Pursuant to Section 553.884, Florida Statutes, strengthening of existing site built, single family residential structures to resist hurricanes shall be provided.

101.1: When a roof of an existing site built, single family residential structure is replaced:

- (a) Roof-decking attachment and fasteners shall be strengthened and corrected as required by section 201.1 (The existing sheathing must be fastened as per section 201.1 and inspected. The inspection must be performed prior to being covered)

I \_\_\_\_\_, understand this requirement for existing sheathing fastening to be strengthened and inspected prior to being covered.

Contractor signature:

\_\_\_\_\_

- (b) A secondary water barrier shall be provided as required by section 201.2. A secondary water barrier shall be installed using one of the following methods when re-roofing. Choose one:

- All joints in roof sheathing shall be covered with a minimum 4" wide strip of self-adhering polymer modified bitumen tape applied directly to the sheathing. (This method is not acceptable on board sheathed roofs.)
- The 30# ASTM D226 or 30# ASTM D2626 tin tagged per the HVHZ Code shall be covered with an approved self-adhering polymer modified bitumen cap sheet.
- The 30# ASTM D226 or 30# ASTM D2626 tin tagged per the HVHZ Code shall be covered with an approved cap sheet applied using an approved hot-mop application. (Owner-builder may not choose this option.)

I \_\_\_\_\_, understand this requirement for the secondary water barrier to be installed and inspected prior to covering.

Contractor signature:

\_\_\_\_\_

\*Dade County Property Appraiser Ad Valorem Taxation Value:  
\_\_\_\_\_ (attach copy)